

**Groundwater Management Area 8 – Desired Future Conditions**

<b>Aquifer</b>	<b>Desired Future Condition (DFC)</b>	<b>Date DFC Adopted</b>
Woodbine	Total average drawdown of 146 feet from 2010 to 2070	1/31/2017
Paluxy	Total average drawdown of 144 feet from 2010 to 2070	1/31/2017
Glen Rose	Total average drawdown of 116 feet from 2010 to 2070	1/31/2017
Twin Mountain	Total average drawdown of 313 feet from 2010 to 2070	1/31/2017
Travis Peak	Total average drawdown of 177 feet from 2010 to 2070	1/31/2017
Hensell	Total average drawdown of 118 feet from 2010 to 2070	1/31/2017
Hosston	Total average drawdown of 206 feet from 2010 to 2070	1/31/2017
Antlers	Total average drawdown of 177 feet from 2010 to 2070	1/31/2017
Edwards (BFZ)	Maintain at least 100 acre-feet per month of stream/spring flow in Salado Creek in Bell County during a repeat of the drought of record. Maintain at least 42 acre-feet per month of aggregated stream/spring flow in Travis County during a repeat of the drought of record. Maintain at least 60 acre-feet per month of aggregated stream/spring flow in Williamson County during a repeat of the drought of record.	1/31/2017
Ellenburger-San Saba	Maintain 90 percent of saturated thickness from 2010 to 2070	1/31/2017
Hickory	Maintain 90 percent of saturated thickness from 2010 to 2070	1/31/2017
Marble Falls	Maintain 90 percent of saturated thickness from 2010 to 2070	1/31/2017

See additional documents submitted by Groundwater Management Area 8 for desired future conditions by groundwater conservation district, county, and outcrop/subcrop of the Northern Trinity and Woodbine aquifers.